

WE ARE KAYO

The Kayo brand was launched in 2002. There was a void in the market for well-built, reasonably priced ATVs and Dirt Bikes. We decided to change that. Our in-house team designed, developed, and manufactured those early models which we sold on the European market. The demand increased, and we started branching out internationally.

From those humble beginnings, we now manufacture over 50,000 units per year. Never losing our focus of building small to medium displacement, off-road motorcycles, and ATVs with exceptional quality and reasonable pricing. We want to get everyone riding again!





ATVs

Kayo ATVs were born out of necessity. Affordable ATVs were inferior and the market seemed to be closed off to those who just want to have fun without spending an arm and a leg.

So we set our sights on changing all that!

The catalog you are holding showcases our latest ATVs. From 70cc up to 200cc, available in sport and utility versions. We stand behind our machines by offering a Warranty that rivals any in the industry.

What are you waiting for? Try out a Kayo, as we say...

Adventure Begins Here!





SPORT FOX 70

ENGINE	70cc SOHC 4-Stroke	FUEL SYSTEM	Carbureted	SEAT HEIGHT	23¾"
START METHOD	Electric	BRAKES	Disc brakes	WHEELBASE	30¼"
COOLING	Air cooled	FRONT TIRE	16 x 8 x 7"	DRY WEIGHT	159 lbs
TRANSMISSION	Automatic	REAR TIRE	16 x 8 x 7"		





SPORT PREDATOR 125

ENGINE 124cc SOHC 4-Stroke START METHOD **Electric** COOLING Air cooled TRANSMISSION Automatic F-N-R

FUEL SYSTEM BRAKES FRONT TIRE **REAR TIRE**

Carbureted Disc brakes 19 x 7 x 8" 18 x 9.5 x 8" SEAT HEIGHT 271/2" WHEELBASE 391/2" 227 lbs. **DRY WEIGHT**





SPORT STORM 150

ENGINE 140cc SOHC 4-Stroke START METHOD **Electric** COOLING

FUEL SYSTEM

Air//remote oil cooler Carbureted

FRONT TIRE **REAR TIRE**

TRANSMISSION **semi-automatic**, 3-spd. w/reverse

SEAT HEIGHT 20 x 7 x 10" WHEELBASE 19 x 10 x 9" **DRY WEIGHT**

BRAKES

Disc brakes 39¼" 269 lbs.





SPORT STORM 180

177cc SOHC 4-Stroke **ENGINE** START METHOD **Electric** COOLING Air cooled **FUEL SYSTEM** Carbureted

TRANSMISSION Automatic

REAR TIRE

CVT, R-N-F FRONT TIRE 20 x 7 x 10" 19 x 10 x 9"

BRAKES SEAT HEIGHT WHEELBASE **DRY WEIGHT**

Disc brakes 320 lbs.





SPORT JACKAL 200

199cc SOHC 4-Stroke **ENGINE** START METHOD **Electric** COOLING Air cooled **FUEL SYSTEM** Carbureted

FRONT TIRE **REAR TIRE**

TRANSMISSION **4-spd. manual** w/reverse

SEAT HEIGHT 20 x 7 x 10" WHEELBASE 19 x 10 x 9" **DRY WEIGHT**

BRAKES

Disc brakes 42¾" 364 lbs.







UTILITY BULL 125

ENGINE 124cc SOHC 4-Stroke TRANSMISSION Automatic BRAKES R-N-F START METHOD **Electric** SEAT HEIGHT COOLING Air cooled FRONT TIRE 19 x 7 x 8" WHEELBASE **FUEL SYSTEM** Carbureted REAR TIRE 18 x 9.5 x 8" **DRY WEIGHT**


G-MONTH LIMITED WARRANTY

Disc brakes

24¾"

35¼"

231 lbs.



START METHOD Electric COOLING Air/remote oil cooler

UTILITY BULL 150

ENGINE

FUEL SYSTEM Carbureted

140cc SOHC 4-Stroke

TRANSMISSION **3-spd. semi auto**

FRONT TIRE **REAR TIRE**

w/reverse

20 x 7 x 10"

19 x 10 x 9"

SEAT HEIGHT WHEELBASE **DRY WEIGHT**

BRAKES

Disc brakes 41¼" 311 lbs.





ATV SPECIFICATIONS

















	FOX 70	PREDATOR 125	STORM 150	STORM 180	JACKAL 200	BULL 125	BULL 150	BULL 200
ENGINE TYPE	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke
DISPLACEMENT	70cc	124cc	140cc	177cc	199сс	124cc	140cc	176cc
FUEL SYSTEM	Carbureted	Carbureted	Carbureted	Carbureted	Carbureted	Carbureted	Carbureted	Carbureted
COOLING	Air cooled	Air cooled	Air & remote oil cooler	Air cooled	Air cooled	Air cooled	Air & remote oil cooler	Air cooled
START METHOD	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
TRANSMISSION	Automatic	Automatic F-N-R	3-spd semi-auto with reverse	Automatic F-N-R	4-spd manual with reverse	Automatic F-N-R	3-spd semi-auto with reverse	Automatic CVT F-N-R
FRONT SUSPENSION	Non-adjustable shocks	Double A-arm	Double A-arm	Double A-arm	Double A-arm	Double A-arm	Double A-arm	Double A-arm
REAR SUSPENSION	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable	Single shock, adjustable
FRONT BRAKES	Disc brake	Disc brake	Dual disc brake	Disc brake	Dual disc brake	Disc brake	Disc brake	Disc brake
REAR BRAKES	Disc brake	Disc brake	Disc brake	Disc brake	Disc brake	Disc brake	Disc brake	Disc brake
FRONT TIRES	16 x 8 x 7"	19 x 7 x 8"	20 x 7 x 10"	19 x 7 x 8"	20 x 7 x 10"	19 x 7 x 8"	20 x 7 x 10"	23 x 7 x 10"
REAR TIRES	16 x 8 x 7"	18 x 9.5 x 8"	19 x 10 x 9"	18 x 9.5 x 8"	19 x 10 x 9"	18 x 9.5 x 8"	19 x 10 x 9"	22 x 10 x 10"
WHEELBASE	30¼"	39½"	39¼"	44"	42¾"	35¼"	41¼"	44"
FUEL CAPACITY	0.5 gallons	0.5 gallons	1.8 gallons	1.45 gallons	1.6 gallons	0.55 gallons	1.8 gallons	2.4 gallons
SEAT HEIGHT	23¾"	27½"	29¼"	30"	31¼"	24¾"	28¾"	30"
GROUND CLEARANCE	41/2"	3½"	5"	6"	3¾"	3½"	5¼"	6¾"
DRY WEIGHT	159 lbs.	227 lbs.	269 lbs.	320 lbs.	364 lbs.	231 lbs.	311 lbs.	397 lbs.
WARRANTY	6 Month Limited	6 Month Limited	6 Month Limited	6 Month Limited	6 Month Limited	6 Month Limited	6 Month Limited	6 Month Limited



UTILITY BULL 200

176cc SOHC 4-Stroke START METHOD **Electric** COOLING Air cooled **FUEL SYSTEM** Carbureted

BRAKES

23 x 7 x 10" REAR TIRE 22 x 10 x 10" Disc brakes

WHEELBASE **DRY WEIGHT** 397 lbs.





Kayo started building dirt bikes in 2002. Since then we have been selling dirt bikes internationally with great success.

We developed the 250cc water-cooled T6 in 2013 and it claimed the Chinese National Championship.

All of our accomplishments and experiences have taught us how to build great dirt bikes. We also understand not everyone is lining up to race. With those riders in mind, we present our 2021 lineup of dirt bikes.

Affordable, reliable, and just plain fun to ride.

What are you waiting for?
Try out a Kayo, and as we say...

Adventure Begins Here!



OFF-ROAD K2 230

ENGINE
START METHOD
COOLING
TRANSMISSION

223cc SOHC 4-Stroke
Electric/kick
Air cooled
5-speed

FUEL SYSTEM Carbureted
BRAKES Disc brakes
FRONT TIRE 80/100 x 21"
REAR TIRE 110/90 x 18"

SEAT HEIGHT 34½"
WHEELBASE 52¾"
DRY WEIGHT 231 lbs.





OFF-ROAD K4 250

ENGINE 250cc SOHC 4-Stroke **FUEL SYSTEM** START METHOD Electric/kick BRAKES FRONT TIRE COOLING Air cooled TRANSMISSION **6-speed** REAR TIRE

Carbureted Disc brakes 80/100 x 21" 110/90 x 19" SEAT HEIGHT 36½" WHEELBASE **DRY WEIGHT** 236 lbs.





OFF-ROAD KT 250

ENGINE 250cc 2-Stroke START METHOD Electric/kick COOLING Water cooled TRANSMISSION **6-speed**

FUEL SYSTEM BRAKES

FRONT TIRE

Carbureted Disc brakes, 240mm disc

80/100 x 21"

REAR TIRE SEAT HEIGHT WHEELBASE

242 lbs.

DRY WEIGHT

110/90 x 18" 3-MONTH LIMITED



OFF-ROAD K6

ENGINE 249cc DOHC 4-Stroke START METHOD Electric/kick COOLING Water cooled TRANSMISSION **6-speed**

FUEL SYSTEM BRAKES

FRONT TIRES

Fuel injected Disc brakes 240mm disc 80/100 x 21"

REAR TIRES SEAT HEIGHT WHEELBASE **DRY WEIGHT**

110/90 x 18" 37½" 58½" 252 lbs.





OFF-ROAD K6-R

ENGINE 249cc DOHC 4-Stroke START METHOD **Electric/kick** COOLING Water cooled TRANSMISSION **6-speed**

FUEL SYSTEM BRAKES

FRONT TIRE

Carbureted Disc brakes, 240mm disc

80/100 x 21"

REAR TIRE SEAT HEIGHT WHEELBASE

DRY WEIGHT

110/90 x 19" 245 lbs.

3-MONTH LIMITED

RIDEKAYO.COM

DIRT BIKE SPECIFICATIONS



	T2	T4	K2	K4	KT 250	K6	K6-R
ENGINE TYPE	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	SOHC 4-Stroke	2-Stroke	DOHC 4-Stroke	DOHC 4-Stroke
DISPLACEMENT	223cc	230cc	223cc	250cc	250сс	249cc	249сс
FUEL SYSTEM	Carbureted	Carbureted	Carbureted	Carbureted	Carbureted	Fuel injected	Carbureted
COOLING	Air cooled	Air cooled	Air cooled	Air cooled	Water cooled	Water cooled	Water cooled
START METHOD	Electric/kick	Electric	Electric/kick	Electric/kick	Electric/kick	Electric/kick	Electric/kick
TRANSMISSION	Manual 5-speed	Manual 6-speed	Manual 5-speed	Manual 6-speed	Manual 6-speed	Manual 6-speed	Manual 6-speed
FRONT SUSPENSION	Inverted forks	Inverted forks					
REAR SUSPENSION	Single shock	Single shock					
FRONT BRAKES	Disc brake	Disc brake 240mm	Disc brake 240mm				
REAR BRAKES	Disc brake	Disc brake 240mm	Disc brake 240mm				
FRONT TIRES	80/100-21"	80/100-21"	80/100-21"	80/100-21"	80/100-21"	80/100-21"	80/100-21"
REAR TIRES	110/90-18"	110/90-18"	110/90-18"	110/90-19"	110/90-18"	110/90-18"	110/90-19"
WHEELBASE	53½"	54"	52¾"	56½"	58½"	58½"	58½"
FUEL CAPACITY	2.5 gallons	1.8 gallons	1.77 gallons	2.6 gallons	1.9 gallons	1.9 gallons	1.8 gallons
SEAT HEIGHT	34½"	38"	34½"	36½"	37½"	37½"	371/2"
GROUND CLEARANCE	11"	131⁄8"	12½"	13"	13½"	13¼"	13¼"
DRY WEIGHT	236 lbs.	236 lbs.	231 lbs.	236 lbs.	242 lbs.	252 lbs.	245 lbs.
WARRANTY	3 Month Limited	3 Month Limited					





ENGINE **56.8cc 4-Stroke single** COOLING Air cooled STARTER **Electric FUEL SYSTEM Carbureted** TRANSMISSION Fully automatic TIRES **2.50/10** front **2.50/10** rear BRAKES **Disc brakes**, front/rear FRONT SUSPENSION Conventional forks REAR SUSPENSION Single shock

SEAT HEIGHT 22 in. WHEELBASE **34.4 in.** FUEL CAPACITY .66 gallon DRY WEIGHT 92.5 lbs.





ENGINE **86cc 4-Stroke single** COOLING Air cooled STARTER Electric/Kick FUEL SYSTEM Carbureted TRANSMISSION Semi-automatic, 4-speed TIRES 2.50/12 front 3.00/10 rear BRAKES **Disc brakes**, front/rear FRONT SUSPENSION Conventional forks REAR SUSPENSION Single shock

SEAT HEIGHT 24.6 in. WHEELBASE 41.5 in. FUEL CAPACITY.92 gallon DRY WEIGHT 123.5 lbs.



ENGINE 120cc 4-Stroke single COOLING Air cooled STARTER Electric/Kick FUEL SYSTEM Carbureted TRANSMISSION Semi-automatic, 4-speed TIRES 60/100-14 front 80/100-12 rear BRAKES **Disc brakes**, front/rear FRONT SUSPENSION Inverted forks REAR SUSPENSION Single shock

30-DAY PARTSONLY

SEAT HEIGHT 29.5 in. WHEELBASE 44.2 in. DRY WEIGHT 143 lbs. FUEL CAPACITY.92 gallon







ENGINE **120cc 4-Stroke single** COOLING Air cooled STARTER Electric/Kick FUEL SYSTEM Carbureted TRANSMISSION **4-speed manual** TIRES **70/100-17** front **90/100-14** rear BRAKES Disc brakes, front/rear FRONT SUSPENSION Inverted forks REAR SUSPENSION Single shock

SEAT HEIGHT 33.6 in. WHEELBASE 48 in. FUEL CAPACITY 1.45 gallon DRY WEIGHT 161 lbs.



ENGINE 140cc 4-Stroke single COOLING Air/oil cooled STARTER Electric/Kick FUEL SYSTEM Carbureted TRANSMISSION 4-speed manual TIRES **70/100-17** front **90/100-14** rear BRAKES **Disc brakes**, front/rear FRONT SUSPENSION Inverted forks REAR SUSPENSION Single shock

30-DAY PARTSONLY

SEAT HEIGHT 33.6 in. WHEELBASE 48 in. FUEL CAPACITY 1.45 gallon DRY WEIGHT 161 lbs.





